

Corrugated Ducts For Anchors



Corrugated ducts in various diameters

SIREG GEOTECH manufactures corrugated ducts using the highest quality raw material, DUROTENE®, a high density polyethylene (HDPE) with extraordinary levels of elasticity and endurance against chemical agents and mechanical strain.

The ducts are produced in different diameters and wall thicknesses. They are shipped in rolls of selected lengths or in bars with lengths based on the clients' request.

SIREG has developed a unique connection system, with male/female terminations every 1,05 meters of pipe. The system is used to connect the corrugated ducts in both formats available, rolls and bars. When supplied in rolls, material waste is significantly reduced by connecting among themselves residual pieces from various rolls. Additionally, by connecting bars, it allows the client to achieve significant transportation cost savings with bar shipments.



Corrugated duct with male/female connection system in roll

CORRUGATED DUCTS FOR ANCHORS

Type	Outer diameter mm	Internal diameter mm	Thickness mm	Packaging
22/28	28	22	1,2	Rolls 200 m
45/55	55	45	1,2	Rolls 250 m
55/65	65	55	1,2	Rolls 250 m
58/70	70	58	1,2/1,5	Rolls 200 m
71/85	85	71	1,2/1,5	Rolls 200 m
86/100	100	86	1,2/1,5	Rolls 150 m
100/114	114	100	1,5	Rolls 100 m
105/117	117	105	1,5	Rolls 100 m